



## Mercury 250 Air Deck

POA



## Specifications

### Boat Details

Price	POA	Boat Brand	Mercury
Model	250 AIR DECK	Length	2.50
Year	2020	Category	Inflatable Boats
Hull Style	Single	Hull Type	Inflatable
Power Type	Power	Stock Number	0
Condition	New	State	Queensland
Suburb	BUNGALOW	Engine Make	

### Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.

## Description

A lightweight, comfortable and versatile boat which holds up to 3 adults and 1 child. The horsepower options that best suit this model, are from 5 to 8hp Mercury Outboards

Fabric Mehler Haku PVC or Achillies HP

Boat Colour Grey / White

Max. persons 3+1 child

Max. HP 8

Transom height Short

Max. engine weight (kg) 40

Max. load (kg) 545

Weight 1 (kg) 35 for Mehler Haku PVC model

39 for Achillies HP model

Length (cm) [outside] 253

Width (cm) [outside] 154

Tube diameter (cm) 40

Number of air chambers 3+Keel+Floor

Keel Inflatable

Floor HP Air Mat

Dimensions of folded boat (cm) - Bag 1102 x 56 x 35

Warranty on fabric and seams 3 years for Mehler Haku PVC model

5 years for Achillies HP model

### Note:

1 Includes weight of oars, does not include weight of seat (where applicable), double action pump, repair kit and carry bag.

Recommended tube air pressure is 0.25bar (3.6psi)

Due to our constant efforts to offer the finest products available, Mercury inflatables reserves the right to change specifications without notice.

Equipment Hull

- Compact & lightweight inflatable boat, ideal boat tender. Easy to carry, comfortable and roomy.
- X Stitch air floor. Thousands of X-stitched fibres give much more rigidity than traditional drop-stitched air floor.

Features non-slip patches for safety.

- Horizontal floor support thrust board.
- Inflatable keel forms a V in bottom of the boat for improved performance.
- Stainless steel towing eyes in transom, make ideal davit lifting points.
- ABS sheet laminated transom, eliminates transom maintenance.
- Inside one way water drain.

### Buoyancy Tube

- Choice of Mehler Haku PVC or Achillies HP fabric.
- 3 separate internal air chambers for safety.
- Semi-recessed air valves - self draining, internal spring-loaded quick seal system, with plug.
- Rounded end cones. Ideal for quicker planning & four stroke outboards, eliminates water backwash and provides better stability.
- Easily accessible internal lifting eyes, make ideal davit lifting points.
- Fold down rowlocks, for neat compact storage of oars and provides room for seating along the tubes.
- Durable grab rope.
- Dragon handles, soft and comfortable.

---

### Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.

- Rub strake
- Combined cleat / grab handle.
- 2 external stainless steel D-rings under the bow
- Bow-eye / handle

#### Standard Equipment

- Storage / carry bag.
- Repair kit.
- Double action hand pump with gauge.
- Aluminium oars.
- Removable fibreglass seat.

#### Optional Accessories

- Bow dodger storage bag.
  - Under seat storage bag.
  - Launching wheels.
  - 12v Bravo automatic electric inflator and deflator.
  - Boat cover.
- 

#### Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.